

# MODELLING PHOTONIC CRYSTAL DEVICES USING SECOND ORDER FINITE VOLUME METHOD

**T. Z. Ismagilov**

Department of Information Technology  
Department of Mathematics and Mechanics  
Novosibirsk State University  
Pirogova 2, Novosibirsk, 630090, Russia  
ismagilov@academ.org

A second order finite volume scheme is considered [1]. The scheme includes total field - scattered field formulation and a perfectly matched layer [2]. It was applied to evaluation of optical properties of photonic crystal waveguides [3]. Reflection and transmission coefficients were studied for a range of frequencies inside the photonic crystal bandgap for different configurations. Our results compare well with simplified analytic models from previous researchers [4].

## References

- [1] S. M. Rao *Time Domain Electromagnetics*, San Diego, Academic Press, 1999.
- [2] J. P. Berenger *A perfectly matched layer for the absorption of electromagnetic waves*, J. Comput. Phys. 114 (1994) pp. 185–200.
- [3] J. D. Joannopoulos, S. G. Johnson , J. N. Winn, R. D. Meade *Photonic Crystals: Molding the Flow of Light*, Princeton University Press, 2008.
- [4] A. Mekis , J. C. Chen , I. Kurland , S. Fan , P. R. Villeneuve , and J. D. Joannopoulos *High Transmission through Sharp Bends in Photonic Crystal Waveguides*, Phys. Rev. Lett. 77 (1996) pp. 3787–3790.